



# Wagon Chassis

Model	Capacity	Track	Front Spindle	Rear Spindle	Axles	Tires	Wheels
CS-08	16,000lbs.	77"	1-3/4"	1-3/4"	3x6x3/16TS	11L-15LRD	15x8 6-6
CS-10	20,000lbs.	79"	2-1/8"	2-1/8"	3x6x1/4TS	11L-15LRD	15x8 6-6
CS-12	24,000lbs.	77"	2-1/4"	2-1/4"	3x8x1/4TS	12.5L-15LRE	15x10 8-8
CT-12	24,000lbs.	79"	2-1/8"	2-1/4"	3x6x1/4TS	11L-15LRD	15x8 6-6
CT-14	28,000lbs.	77"	2-1/4"	2-1/2"	3x8x1/4TS	12.5L-15LRE	15x10 8-8

*Optional 8" Extended Wide-Track and Spring-Assist Tongue Lift are available.*

### Standard Features:

- Double Reach Poles for Greater Stability and Truer Tracking
- Heavy Duty Steel Tube Axle Beams
- Reinforced Spindle Design
- Tapered Roller Bearings
- Greasable Bushings at all Wear Points
- Tie Rod Ends - Teflon® Lined Ball Joints with 3/4" Stud
- Kingpin Bolt - 1" Grade 8 w/Sintered Bronze Bushings
- Tongue Bolt - 7/8" Grade 8
- Automotive Type Steering
- Easy Hitch - Pull Out Tongue
- Convenient Rear Hitch
- Reach Poles - 2-1/2 Sch. 40 Pipe (2-7/8" OD)
- Bolster Stakes - Set at 42"
- Epoxy Primer & Polyurethane Paint

